

HALO - Shadow / Solar / Sync / set

H003

Versatile chest harness, sit harness and ascender modular combination for rope access

SOLAR chest harness features:

- Lightweight construction
- Replaceable ascender connection
- Connection orientates ascender close to the chest
- Front attachment point
- Simple to adjust

SHADOW harness features:

- Low profile waist and leg padding
- Large waist D-ring for multiple attachments
- Reinforced gear loops with 20kg SWL
- Elasticated rear leg loop straps

SYNC ascender features:

- X-Cam technology
- Does not jam, even against knots
- Provides high degree of grip on ropes of varying condition including after rupture of sheath
- Attaches directly to harness
- Secure, stable and comfortable - performs like part of the harness
- Removable

X-Cam has a more advanced tooth design than traditional cams and is more suitable for industrial applications as it does not pluck the rope, so reducing rate of rope wear.

Sync attaches directly to the SOLAR chest harness, no extra connectors are required.

Sits tightly against the chest section for efficient ascending. Attachment points reduce movement to an absolute minimum for optimum comfort and efficiency.

Ascender is removable for replacement, no tools are required, simply remove the harness connector and unhook the Sync.

Harness size option: standard



Patent Pending GB1808077.0

Specifications:

NB: specifications and colour may change without notice.

Size: Standard (Harness) / 10.5 - 12mm rope (Ascender)	Attachment Points:
EN Test Mass: 140kg (Chest Harness when attached to Shadow harness) / 140kg (Harness) / 125kg (Ascender)	Sternal Waist
Loading:	
Conformity: EN361 (Chest - when attached to Shadow), EN813 (Harness) / EN 567, EN 12841(B) (Ascender)	Harness Measurements (cm):
Materials: Polyamide, steel, aluminium	Torso 95-120
Weight (kg): 2.20	Waist 70-140
Industries: Rope access	Thigh 60-80